# AD-A250 389



NPS-PH-92-007

## NAVAL POSTGRADUATE SCHOOL

Monterey, California





Amending the w. Velocity Scale for Surface Layer, Entrainment Zone, and Baroclinic Shear in Mixed Forced/Free Turbulent Convection

by

R.F. Kamada

March 1992

Final Report for Period October 1990 - September 1991

Approved for public release; distribution unlimited

Prepared for: U.S. Air Force, Space Division,
Los Angeles AFB, California 90009

92-13744



### NAVAL POSTGRADUATE SCHOOL Monterey, California

Rear Admiral R. W. West Superintendent

H. Shull Provost

The work reported herein was prepared for and funded by U.S. Air Force Space Systems Division, Los Angeles, CA, 90009.

Reproduction of all or part of this document is authorized.

This report was prepared by

R. F. KAMADA,

Adjunct Research Professor of Physics

Reviewed by:

K. E. Woehler,

Chairman,

Department of Physics

Released by:

Paul J. Marto,

Dean of Research

SECURITY (	LASSECATO	ON OF THIS PA	AGE

REPORT DOCUMENTATION PAGE			Form Approved CMB No. 0704-0188		
1a REPORT SECURITY CLASSIFICATION		16 RESTRICT VE MARKINGS			
UNCLASSIFIED					
2a SECURITY CLASSIFICATION AUTHORITY			AVA LABILITY OF		
26 DECLASSIFICATION DOWNGRADING SCHEDU	LE	approved for public release; distribution unlimited.			
4 PERFORMING ORGANIZATION REPORT NUMBE	ER,S)	5 MONITORING	DRGANZATION RE	POPT NU	₩3EP:S/
NPS-PH-92-007					
6a NAME OF PERFORMING ORGANIZATION	6b OFFICE SYMBOL (If applicable)	7a NAME OF MO	ON TORING OPGAT	√ZAT ÚN	
	(iii applicable)	USAF Space	Systams Div	ricion	
6c ADDRESS (City, State, and ZIP Code)	J	USAF Space Systems Division  7b ADDPESS(City, State and ZiP Code)			
		Los Angeles	AFB, CA	90009	
8a NAME OF FUNDING SPONSORING ORGANIZATION	8b OFFICE SYMBOL (If applicable)	9 PROCUREVENT	NSTRUMENT DE	ENTECAT	ON NUMBER
USAF Space Systems Div.	USAF/SSD	MPTP DV7614	MPIR FY76169100412		
8c. ADDRESS (City State, and ZIP Code)	CORT/OOD	10 SO PCE OF F		5	
		PROGRAM	2507£C_	TASK	#OFE UNIT
V - A - 1 - AFR GA 00000		ELEMENT NO	^• <u></u>	NO	ACCESSION NO
Los Angeles AFB, CA 90009		<u> </u>		L	<u></u>
AMENDING THE W* VELOCIT. SCALE	FOR SURFACE LA	YER, ENTRAIN	MENT ZONE,	AND BA	AROCLINIC SHEAR
IN MIXED FORCED/FREE TURBULENT					
12 PERSONAL AUTHOR(S) R. F. Kamada					
13a TYPE OF REPORT 13b TIME CO	OVERED.	14 DATE OF REPO	RT (Year Month )	Oaul 1:5	PAGE COUNT
technical FROW 10		920330	( Tear, Month	30,7	14
16 SUPPLEMENTARY NOTATION					
17 COSAT CODES	18 SUBJECT TERMS	Continue on reverse	of necessary and	identify t	by block rumber)
FIELD GROUP SUBIGEOUP	Convective Bo		•		
	convection so				
19 ABSTRAC* (Continue on reverse if necessary	and death by black a			·	
					. , , , ,
We amend the free convective m turbulence from forced convect	ion was been	ocity scale, Discrete surf	* to W*s t	o incl	inment zone
and baroclinic components and	requires the le	ength scales:	zo. L. Ah	ential	and zr. a
newly defined baroclinic lengt	h. To close th	e system we	offer simpl	e mode	els for Ah. the
entrainment zone depth. The $\Delta$	h models show r	ealistic diu	rnal hyster	esis,	using a
critical bulk Richardson numbe	r which exceeds	unity.			
20 DISTRIBUTION AND LABILITY OF ABSTRACT		12: 39070-27-572	2116 100 500	* / 15	
NCLASS FED NUMBER DE SAME AS P	PPT	21 ABSTRACT SEC UNCLASSIFIE		( ' <b>∀</b> ¥	
22a NAME OF PESPONS BLE NO VIOUAL R. F. Kamada		226 TELEPHONE (H (408) 646-2	nclude Area Code)	220 OF-	- CE J. D.Box.
DD Form 1473, JUN 86	Previous editions are				of the first of the same of th
2	S/N 0102-LF-0		UNCLASSIFI		· · · · · · · · · · · · · · · · · · ·

#### INTRODUCTION

Deardorff's (1972) similarity theory for convective boundary layers (CBL)s suggests that CBL parameters are controlled by buoyancy,  $\beta \equiv g/\theta$ , (where g is gravitational acceleration and  $\theta$  is potential temperature), surface temperature flux, w' $\theta'_0$ , height z above the surface, and  $z_i$ , the height of the inversion base which marks the top of the mixing-layer (ML). The velocity, temperature, and humidity scales:  $w_z$ ,  $u_z^{ML}$ ,  $\theta_z^{ML}$ ,  $q_z^{ML}$ , formed from these parameters are used in universal relationships for the gradients and fluxes of mean and turbulent quantities in the CBL. The first of these, the convective turbulence scaling velocity

$$W_* \equiv (\beta z_i \overline{w'\Theta'}_0)^{1/3} , \qquad (1)$$

determines much of CBL physics, including diffusion. Along with w'θ'0, w. forms the basis for the remaining parameters used to scale the heat, moisture, and momentum, as well as passive scalar fluxes. However, w. neglects mechanical turbulence due to shear and is only strictly valid for free convection induced by surface heating. Yet, w. is used often in mixed forced/free convection cases for lack of alternatives. Here we seek w\*s, an amendment to w., which includes mechanical turbulence contributions under mixed forced/free convection conditions. We assume mechanical generation comes from three sources: the barotropic, horizontally homogeneous surface layer (SL), barotropic boundary layer entrainment zone (EZ), and a baroclinity (BC) component. the z and z length scales, we propose that mixed forced/free convection also depends on the SL roughness length,  $z_0$ , SL Obukhov length,  $L = -u_*^3\theta/(gkw'\theta'_0)$  (where  $u_*$  is friction velocity and k = 0.4 is the von Karmen constant), EZ thickness,  $\Delta h$ , and zh, a baroclinic length scale which we define below. We model these mechanical sources, using relevant ratios of the length scales, thereby fulfilling similarity requirements.

#### APPROACH

We outline the basic approach before discussing details. For non-baroclinic, horizontally homogeneous, steady state cases, the vertical profiles of the buoyancy and momentum fluxes must be linear, if the shapes of the vertical profiles of potential temperature and wind speed are to remain static. That is,

$$\beta \overline{w'\Theta'}_{z} \simeq \beta \overline{w'\Theta'}_{0} (1 - (1 + a_{1})z/z_{i}) , \qquad (2a)$$

$$-\overline{u_i'w'}_i = -\overline{u_i'w'}_0(1 - (1 + a_2)z/z_i)$$
, (2b)

where  $a_1 = -w'\theta'_{zi}/w'\theta'_0$  and  $a_2 = u_i'w'_{zi}/u_i'w'_0$  (see fig. 1). The subscripts "zi" and "0" refer to conditions at the inversion base and surface.  $-u'w'_0 \equiv u_*^2$ ,  $w'\theta'_{zi} \sim \text{We}_\Delta\theta$ , and  $-u_i'w'_{zi} \simeq \Delta u_i \text{We}$ , where the CBL entrainment rate, We =  $z_{i,t}$  and  $\Delta\theta$  is the potential temperature jump across the EZ. The subscript ",t" denotes the partial derivative with respect to time. Such notation will refer to spatial and temporal derivatives in general. The Betts (1974) correction,  $w'\theta'_{zi} \simeq (\Delta\theta - \Gamma_u\Delta h) \text{We}$ , hardly affects eqn. 2a since Kamada (1988a) showed that the much smaller interfacial thickness,  $l_m$ , must replace the EZ depth,  $\Delta h$ . For lack of better information, we assume that above  $z_i$  the barotropic flux profiles are linear with height up to  $H \equiv z_i + \Delta h$ , the top of the boundary layer. I.e.,

$$\beta \overline{W'\Theta'}_{z} = \beta \overline{W'\Theta'}_{z_{i}} (1 - \frac{z - z_{i}}{\Delta h}) , \qquad (3a)$$

$$-\overline{u_{i}'w'}_{z} = -\overline{u_{i}'w'}_{zi}(1 - \frac{z - z_{i}}{\Delta h}) \qquad . \tag{3b}$$

Using eqns. (1), (2a), and (3a), the vertically integrated buoyancy flux or total CBL buoyancy production rate of turbulence kinetic energy (TKE) can be written to show that the purely free convective turbulent scaling velocity is proportional to the cube root of the boundary layer integrated TKE production rate,

$$\int_{z0}^{H} \frac{1 - a_1(1 + \alpha)}{2} dz \approx 0 \quad w_*^3 \quad \text{where } 0 \equiv \frac{1 - a_1(1 + \alpha)}{2} \quad , \quad (4)$$

and  $\alpha \equiv \Delta h/z_i$ .  $\Omega \simeq 0.4$  for mature CBLs because under such conditions,  $a_1 \sim 0.2$  and  $\alpha \sim 0.1$ . Since this may not be true for other conditions, we discuss  $\Omega$  in detail below. However, here we propose that this sort of proportionality extends to shear; that mechanical contributions to a shear inclusive turbulent scaling velocity,  $w_{*s}$ , may be written in terms of the boundary layer integrated mechanical generation rate of TKE. I.e.,

Accession For

NTIS GRA&I

DTIC TAB

Unannounced

Justification

By

Distribution/

Availability Codes


Avail and/er

Dist

Special

3

fig.1 Schematic profiles of a) buoyancy, b) stress, c) U velocity, and d) TKE shear generation rate for barotropic case



We also propose that the CBL shear generation rate can be represented by discrete barotropic surface layer (SL), entrainment zone (EZ), and baroclinic (BC) components.

$$\int_{z_0}^{H} \frac{\int_{z_0}^{-u_i'w'} u_{i,z} \partial z}{\int_{z_0}^{-u_i'w'} u_{i,z} \partial z} + \int_{z_0}^{H} \frac{\int_{z_0}^{-u_i'w'} u_{i,z} \partial z}{\int_{z_0}^{-u_i'w'} u_{i,z} \partial z} + \int_{z_0}^{H} \frac{\int_{z_0}^{-u_i'w'} u_{i,z} \partial z}{\int_{z_0}^{-u_i'w'} u_{i,z} \partial z}$$
(6)

Here  $u_{ib,z}$  is just the baroclinic portion of the vertical shear.

#### BAROTROPIC SURFACE LAYER SHEAR

We first consider the barotropic SL and assume that most of the shear occurs below the height, -L. From SL similarity we have

$$u_{,z} = (u_*/kz)\phi_m$$
 , with  $\phi_m = (1 - 15z/L)^{-1/3}$  , (7a,b)

(Carl et al. 1973). Some workers prefer  $\phi_{\rm m}$  formulas involving the -1/4 power. However, the choice is among empirical expressions and integrals of -1/4 power expressions result in awkward complex numbers. The accepted value in the free convection limit is -1/3, so we choose this for theoretical appeal as well as mathematical convenience.

Since  $\phi_m$  is only valid for  $z >> z_0$ , we set the upper integration limit at -L, the lower limit at a somewhat arbitrary 10  $z_0$ , and treat the layer below 10  $z_0$  separately. Above 10  $z_0$ , from eqns. (2b) and (7a), we have

$$\int_{10z0}^{-L} \frac{u_{i,z} \partial z}{u_{i,z} \partial z} \simeq \frac{u_{*}^{3} - L}{k} \int_{10z0}^{\phi_{m} \partial z} + \frac{u_{*} (u_{*}^{2} - \Delta u_{i} We)}{k z_{i}} \int_{10z0}^{-L} \phi_{m} \partial z$$

$$\simeq \frac{u_{*}^{3} - L}{k} \int_{10z0}^{\phi_{m} \partial z} - (1-a_{2}) (L/z_{i2}) w_{*}^{3} \int_{10z0}^{\phi_{m} \partial z} \phi_{m} \partial z$$

$$= \frac{u_{*}^{3} - L}{k} \int_{10z0}^{\phi_{m} \partial z} - (1-a_{2}) (L/z_{i2}) w_{*}^{3} \int_{10z0}^{\phi_{m} \partial z} \phi_{m} \partial z$$
(8)

From the L definition,  $u_*^3/k = (-L/z_i)w_*^3$ . With the axes aligned with the mean wind, we have  $-u'_iw'u_z = -u'w'u_z$ , since  $(v_z, w_z) << u_z$  in the mixed layer. If shear supplies sufficient TKE, 10  $z_0 <<< -L$ . So in eqn. (8) term (2) = 0.54 (1 -  $a_2$ )  $(L/z_i)^2w_*^3$ . Letting p = -15z/L, the first integral reduces to

$$\simeq \sqrt{3} \text{ ATAN} \left[ \frac{\sqrt{3(2(p+1)^{1/3} + 1)}}{3} \right] - \frac{\text{Ln}[(p+1)^{2/3} + (p+1)^{1/3} + 1]}{2} + \frac{1}{2}$$

The upper limit evaluates to  $\simeq 1.51$ . The first two terms in the lower limit  $\simeq 1.26$ , if L >>  $150z_0$ . So in eqn. (8) the first integral  $\simeq 0.25$  - Ln R, where R  $\equiv (1-150z_0/L)^{1/3}-1 << 1$ . A 5cm  $z_0$  and 150m L would give 150  $z_0=-0.05L$ . Above 10  $z_0$ , this leads to  $\simeq 4.36u_*^3/k$  from term (1) in eqn. (8). Oddly, R varies inversely with roughness length. But from  $u_*=ku/(\ln(z/z_0-\varphi_m))$  and the definition of L, we see that

$$nz_0/L = (ngw'\theta'/k^2u^3\theta)z_0(ln(z/z_0) - \varphi_m)^3$$
 (9)

So for given levels of u,  $\overline{w'\theta'}$ ,  $\theta$ , and z, the ratio  $nz_0/L$  and thus term (1) may vary much less than  $z_0$  itself.

Below 10  $z_0$  we neglect non-neutral contributions to  $u_*$  and assume a constant value,  $-u_i$ 'w'u,  $\simeq u_*^3/10kz_0$ . Then

$$\int_{0}^{10z0} -\overline{u_{i}'w'}u_{,z}\partial z \approx u_{*}^{3}/k \qquad (10)$$

Together, eqns. (8) and (10) give an estimate of the vertically integrated SL shear production rate,

$$\int_{0}^{-L} \frac{1}{-u_{1}'w'} u_{1,2} \partial z \approx (1.25 - \text{Ln R}) u_{*}^{3}/k ,$$

$$\approx (-w_{*}^{3}L/z_{1}) (1.25 - \text{Ln R}) . \qquad (11a,b)$$

Note that we have dropped term (2) from eqn. (8), since 1) the coefficient is an order of magnitude smaller than for term (1), 2) term (2) is second order in  $z_i$ , 3) usually,  $-L < 0.4 z_i$ , and 4)  $a_2$  is of order  $10^{-1} - 1$ ; so some further cancellation occurs.

From eqns. (2) and (3), if  $\cap = 0.4$ , we have the following ratio of enhanced to unenhanced TKE contributions,

$$\left[\frac{\Omega - (1.25 - \text{Ln R})L/z_{i}}{\Omega}\right]^{1/3} w_{*} \simeq (1 + (3.1 - 2.5\text{Ln R})(-L/z_{i}))^{1/3}w_{*}.$$
(12)

For our previous example,  $w_{*s}$  exceeds  $w_{*}$  by a factor of  $\approx$  (1 +  $33u_{*}^{3}/w_{*}^{3})^{1/3}$ . In this case, since  $u_{*}/w_{*} \approx 0.54$ , SL shear generation alone may enhance  $w_{*s}$  by more than 80%.

To be useful,  $w_{*_5}$  should maintain the same proportion to the mean turbulent velocity,  $\sigma_{ui}/3$ , in both the convective and neutral limits. We test this by noting for the barotropic case that the cube root of the vertically integrated production rate is usually  $\simeq 2.4$  u. for SL shear. The EZ and BC terms are not relevant for the pure neutral case. From Grant (1986) and Mason and Thompson (1987), we find that  $\sigma_{ui}/3 \simeq 1.3$  u. in the layer averaged neutral boundary layer. This implies that  $\sigma_{ui}/3 \simeq 0.53$  w. In the pure convective limit, the CBL averaged value for  $\sigma_{ui}/3$  is  $\sim 0.55$  w. (Caughey and Palmer, 1979 and Deardorff et al. 1980). So, the ratio of w.s to the layer averaged mean turbulent velocity is the same in the convective and neutral limits, as required.

#### ENTRAINMENT ZONE SHEAR

The EZ also generates mechanical turbulence. To quantify it we assume, moreover, that shear is constant across  $\Delta h$ . Thus,

$$\int_{z_i}^{H} \frac{1}{-u_i'w'} u_{i,z} \partial z \approx We \Delta u_i^2 / 2 \qquad (13)$$

Equation (13) suggests the need for a simple shear inclusive model to estimate the entrainment rate, We. For this purpose we parameterize the TKE equation,

storage buoyancy transport shear dissipation 
$$e_{,t} = \beta \overline{w'\theta'} + (\overline{u_i'e} + \overline{p'e/\rho})_{,z} - \overline{u_i'u_j'u_{i,j}} - v\overline{u_{i,j}u_{i,j}} , \qquad (14)$$

at the inversion base as,

storage buoyancy transport shear dissipation 
$$C_{st}w_*^2We/\Delta h \simeq -\beta\Delta\Theta We + C_cw_*^3/z_i + C_m\Delta u_i^2We/\Delta h - C_dw_*^3/z_i \ . \tag{15}$$

The scaling arguments are that 1) again  $\overline{w'\theta'}_{zi} \simeq -We \Delta\theta$  and 2) large mixed layer eddies drive the TKE transport rate into the EZ. Thus TKE transport should vary with the TKE ( $\propto w_*^2$ ) times the large eddy turnover time scale,  $z_i/w_*$ . 3) The shear production rate is modeled as the momentum flux, Au, We, times the local EZ shear,  $\Delta u_i/\Delta h$ . 4) To maintain a steady state inertial subrange, the dissipation plus buoyancy destruction rates must balance the large eddy TKE injection rate due to transport and shear production. So in the neutral limit, dissipation should scale like transport with the change rate of large eddy TKE,  $w_*^3/z_i$ . Since dissipation occurs at small scales, unaffected by buoyancy anisotropy, we retain the neutral form. For simplicity we neglect the small TKE storage rate term.  $C_{\rm m}$  estimates vary somewhat, (Pollard et al. 1981; Kato and Phillips, 1967, Tennekes and Driedonks, 1981), but we see little reason for departures far from unity, so we assume  $C_m \sim 1.0$ . We discuss  $C_c$  and  $C_d$  below.

Tennekes and Driedonks (1981) presented a similar model, except that here we scale the shear production locally with  $\Delta h$  instead of z. Solving for the entrainment rate gives,

We = 
$$\frac{(C_c - C_d)}{\beta \Delta \theta - \Delta u_i^2 / \Delta h} w_*^3 / z_i \qquad (16)$$

Therefore, from eqn. (13) we have

$$\int_{z_{i}}^{H} \frac{-u_{i}'w'u_{i,z}\partial z}{2(R_{b}-1)} = \frac{(C_{c}-C_{d})}{2(R_{b}-1)} \frac{\Delta h}{z_{i}} w_{*}^{3} , \qquad (17)$$

where the bulk Richardson number,

$$R_{b} \equiv \frac{\beta_{\Delta}\Theta_{\Delta}h}{\Delta u_{i}^{2}} \qquad (18)$$

The EZ is transitionally turbulent by nature. Thus, we expect  $R_{\text{ch}}$  to fluctuate about some critical threshold turbulence value,  $R_{\text{ch}}$ .  $R_{\text{ch}}$  is much larger than the 1/4 value accepted for the stable SL because EZ TKE is mainly maintained by large eddy transport from below. So shear generation is only part of the TKE injection rate, and the dominant eddies are also much larger than in the transitionally turbulent SL. Thus, the EZ's large negative buoyancy will destroy much of the TKE during the eddy cascade before it can be dissipated at small scales. For these reasons

R<sub>ch</sub> may exceed unity in the EZ.

Indeed, our simulations to steady state using such an entrainment model suggest a typical value of  $R_{cb} \approx 1.3$ . From the results of Turner (1968), Deardorff et al. (1980), and many others, we suggest that  $C_c - C_d \approx 0.25$  in the convective limit. So in eqn. (17) the EZ shear contribution  $\approx 0.5 \ \alpha w_*^3$ , where  $\alpha \equiv \Delta h/z$ .

To assume that  $\alpha \simeq 0.1$  – 0.2 may often suffice. Then,  $a_1 \simeq 0.2$ ,  $\Omega \simeq 0.4$ , and the barotropic EZ contribution to  $w_{*_S}$  is only a few percent. But  $\alpha$  can exceed unity during rapid entrainment into a near-neutral layer remaining from the previous day's CBL (Nelson et al. 1989). During such times, entrainment models suggest that  $a_1$  may exceed 40% (Kamada, 1988a). Then  $\Omega \simeq 0.1$ , and EZ enhancement of  $w_{*_S}$  may exceed 0.4. With SL shear this may cause  $w_{*_S}$  to double. In this case a better diagnostic or prognostic estimate for  $\alpha$  is needed. For a diagnostic estimate, we begin by assuming  $R_b = R_{cb}$  and solve eqn. (17) for  $\Delta h$ . This leaves unknown  $\Delta u_i$  and  $\Delta \theta$ , the inversion temperature jump.  $\Delta \theta$  is hard to specify more precisely than  $\sim +/-$  30% because  $z_i$  and H are not that highly resolved. Yet, we know that  $\Delta \theta$  grows with the boundary layer growth rate,  $H_{i}$ , into the layer aloft (with lapse rate  $\Gamma_u$ ), and shrinks with the mixed layer warming rate,  $\theta_{m,t}$ . So, using the simplest steady state assumption,

$$\Delta\Theta_{,t} = \Gamma_{u}H_{,t} - \Theta_{m,t} = 0 \qquad . \tag{19}$$

The mixed layer warming rate is given by the surface heating rate, plus the entrainment rate of warm air from aloft. i.e.,

$$\Theta_{m,t} = \left(\overline{w'\Theta'}_0 - \overline{w'\Theta'}_{z_1}\right)/z_i \qquad (20)$$

So, if we approximate  $H_{,t}$  as We(1 +  $\alpha$ ), we have

$$\Delta \Theta = \overline{w'\Theta'}_0 / We - \Gamma_u z_1 (1 + \alpha) . \qquad (21)$$

Using eqns. (16) and (18) and combining constants, this results in two solutions for  $\alpha$ . We show only the physical root,

$$\alpha = \left[ \frac{2.3 \Delta u_i^2}{\Gamma_u \beta z_i^2} + \frac{1}{4} \right]^{1/2} - \frac{1}{2} \qquad (22)$$

Though not explicit, eqn. (22) implicitly involves  $\Delta\theta$  because it presumes through eqns. (18 - 22) that  $\Delta\theta$  depends on  $\Gamma_u$ , We, w' $\theta'_0$ , and  $z_i$ . This assumes that the capping inversion requires finite potential temperature and windspeed jumps, whenever there is horizontal wind.

In eqn. (22) we must still estimate the windspeed jumps across the EZ. Wyngaard (1988) proposed the following first order estimate. For steady flow over a horizontally homogeneous surface, the stress gradient is given by

$$-\overline{u'w'}_{,z} = f(v - v_g)$$
 , and  $-\overline{v'w'}_{,z} = f(u_g - u)$  , (23a,b)

where f refers to Coriolis forcing, and the subscript, g, refers to geostropic winds (Panofsky and Dutton, 1984). For barotropic flow with the axes aligned with the mean mixed-layer wind,

$$-u'w'_{.z} = fv_g \approx (We(u_g - u) + u_*^2)/z_i$$
 , and  $-v'w'_{.z} = f(u_g - u) \approx We(v_g - v)/z_i$  . (24a,b)

The momentum balance becomes

$$We(u_g - u) + u_*^2 = -fz_iv_g$$
 , and

-We 
$$v_g = f z_i (u_g - u)$$
 . (25a,b)

For barotropic cases, if  $\Delta u = (u_g - u)$  and  $\Delta v = (v_g - v)$  across the EZ, then the solutions to eqns. (25a,b) are to first order,

$$\Delta u = We(u_*/fz_i)^2$$
 , and

$$\Delta V = u_*^2/fz_1 \qquad (26a,b)$$

Here, almost all of the EZ shear results from turning the wind into the v direction. So for a mature mid-latitude BL with  $u_*=0.4\text{ms}^{-1}$ ,  $f=10^{-4}\text{s}^{-1}$ ,  $z_i=10^{3}\text{m}$ ,  $\theta=300$  °C, and  $\Gamma_u=3\times10^{-3}$  °C m<sup>-1</sup>, we have  $\alpha=0.057$ . However, during growth into the near neutral remnant mentioned earlier, conditions may be more like  $\Gamma_u=1\times10^{-3}$  °C m<sup>-1</sup>, and  $z_i=500\text{m}$ . This would result in  $\alpha=1.3$ . Values spanning such a range were reported in Nelson et al. (1989). They also observed and prognostically modeled the typical early morning to late afternoon hysteresis found in plots of  $\alpha$  versus We/w<sub>\*</sub>. They noted that such hysteresis is absent from previous

diagnostic expressions for the EZ depth which have the form  $\alpha \propto \mathrm{Ri}_*^n$ , where  $\mathrm{Ri}_* \equiv \beta z_i \Delta \theta / w_*^2$  and  $1/4 \leq n \leq 1$ . No hysteresis occurs in such expressions, if we assume (see eqn. 2a) that  $a_1$ , the inversion to surface heat flux ratio, is constant because then  $\mathrm{We}/\mathrm{w}_* \propto 1/\mathrm{Ri}_*$ . Unlike such expressions, eqn. (22) shows qualitatively appropriate hysteresis. In fact, by combining eqns. (16), (21), (22), and (26), we see that

$$\frac{\alpha}{We/W_*} \simeq \frac{u_*^4 W_*}{W' \Theta'_0 \beta f^2 z_i^3} . \tag{27}$$

Far from being constant,  $\alpha w_*/We$  will typically increase initially as surface heating and  $u_*$  grow in the young day-time boundary layer, but will diminish later as  $z_i$  becomes large.

If we require more accuracy, we can couple eqns. (16, 18, 19, 20, and 26) with

$$H_{,t} \approx We + (R_{ch}/\beta) \left[ \frac{2u^2 \Delta v We}{f z_i^2 \Delta \theta} - \frac{\Delta v^2 \Delta \theta_{,t}}{\Delta \theta^2} \right]$$
 (28)

to provide a complete entrainment model. Here the second term in eqn. (28) gives the growth rate of  $\Delta h$  and thus a prognostic estimate for  $\alpha$ .

More physics may be added by revising the We expression to include the small TKE storage rate term,  $C_{st}w_*^2/\Delta h$ , from eqn. (16). However, our present focus is amending  $w_*$ , rather than refining the particulars of bulk entrainment models; so we choose to rest with the above diagnostic and prognostic formulations for  $\alpha$ .

In either case, hysteresis in  $\alpha$  versus We/w. is evident, and like Kamada (1988b, figs. 1 and 2), depends on changes in  $\Delta\theta$  and  $z_i$ . Both models include shear as well as heating due to entrainment, and avoids ad hoc surface temperature distributions, or fixed values of  $a_i$ . Also note that eqns. (16) and (21) lets us specify  $a_i$  which, together with eqn. (22), determines  $\Omega$  from eqn. (4).

#### BAROCLINIC SHEAR

If the geostrophic wind varies linearly with height according to the thermal wind relations,  $u_{g,z} = -(g/fT_0)T_{,y}$ , and  $v_{g,z} = (g/fT_0)T_{,x}$ , then from eqn. (23) the baroclinic stress profile must be parabolic, rather than linear as in the barotropic case. Wyngaard (1985) gave the following simple estimate for baroclinic

shear based on the thermal wind,

$$u_{b,z} = b_1 u_{g,z} + b_2 v_{g,z}$$
 ,  $v_{b,z} = b_2 u_{g,z} + b_1 v_{g,z}$  , (29a,b)

where  $b_1 = 1/(m^2 + 1)$ ,  $b_2 = m/(m^2 + 1)$ ,  $m = fz_i/w_*$ , and f is the Coriolis forcing. If so, the stress can be written as

$$-\overline{u_i'w'} = u_*^2 + \frac{b_2 z (gz \rho fT_{,y} + 2 fT p_{,y})}{2 \rho fT} . \qquad (30)$$

So the baroclinic shear contribution becomes

$$\int_{0}^{H} \frac{gz_{i}(b_{2}T_{,x} - b_{1}T_{,y})(b_{2}g\rho z_{i}^{2}T_{,y} + 6\rho Tu_{*}^{2})}{6 \rho f T^{2}},$$
(31)

where terms in  $b_i$  – 1 =  $-m^2/(m^2+1)$  were considered neglectably small. The baroclinic integral is taken over the whole vertical range 0 to  $z_i$  rather than -L to  $z_i$  because the SL shear analysis only accounts for barotropic effects based on SL similarity. Scaling analysis of eqn. (31) shows that the squared and cubic terms in  $z_i$  are small. If so, to first order, the baroclinic shear contribution from eqn. (31) reduces to,

$$\int_{0}^{H} -\overline{u_{i}'w'}u_{i,z}\partial z = (z_{i}/z_{b})w_{*}^{3} , \qquad (32)$$

where we can define a baroclinic length scale as,

$$z_{b} = \frac{fT \ w_{*}^{3}}{u_{*}^{2}g(b_{2}T_{,x} - b_{1}T_{,y})} = \frac{w_{*}^{3}}{u_{*}^{2} u_{b,z}}.$$
 (33)

Usually,  $z_b >> z_i$ . But in coastal areas mesoscale temperature and pressure gradients are often large. For a coastal  $z_i$  of 300 m, a 3 °C/100 km horizontal cross-wind temperature gradient, We near zero,  $f = 10^{-4} \text{ sec}^{-1}$ ,  $w_* \simeq 0.8 \text{ m s}^{-1}$ , and  $u_* \simeq 0.4 \text{ m s}^{-1}$ , then  $z_b \simeq 330 \text{ m}$ , and  $w_*$  may be enhanced baroclinically by  $\sim 50\%$ .

#### SUMMARY

In summary, we account for surface layer (SL), entrainment zone (EZ), and baroclinic (BC) shear. Each source is given in terms of a dimensionless ratio of the relevant length scales  $z_0$ , L,  $_{\Delta}h$ ,  $z_i$ , and  $z_b$ . When summed and multiplied by  $w_*$ , this results in a turbulent velocity scale which includes both buoyancy and shear generation of TKE, namely,

$$W_{*_{S}} \equiv \begin{bmatrix} \bigcap - (1.25 - \ln R) L/z_{i} + 0.5\Delta h/z_{i} + z_{i}/z_{b} \\ \bigcap \end{bmatrix}^{1/3} W_{*} . \tag{34}$$

Here 
$$\cap \equiv \frac{1 - a_1(1 + \alpha)}{2}$$

$$a_1 \simeq Wea\theta/w'\theta'_0$$
 , the  $z_i/surface heat flux ratio,$ 

We 
$$\simeq \frac{(C_c - C_d)}{\beta \Delta \theta - \Delta u_i^2/\Delta h} w_*^3/z_i$$
, the ML entrainment rate,

$$\Delta\theta \simeq \overline{w'\theta'}_0/We - \Gamma_u z_i(1 + \alpha)$$
 , the EZ  $\theta$  jump,

$$\alpha \equiv \Delta h/z_i \simeq \left[ \frac{2.3(\Delta u^2 + \Delta v^2)}{\Gamma_u \beta z_i^2} + \frac{1}{4} \right]^{1/2} - \frac{1}{2} , \text{ the EZ/BL depth ratio,}$$

$$\Delta u = We(u_*/fz_i)^2$$
 ,  $\Delta v = u_*^2/fz_i$  , the EZ velocity jump,

$$R \equiv (1 - 150z_0/L)^{1/3} - 1$$
 , an SL shear generation term,

$$z_b \equiv \frac{w_*^3}{u_*^2 u_b}$$
 , the baroclinic length scale.

#### REFERENCES:

Betts, A.K., 1974: Reply to comment on the paper, 'Non-precipitating cumulus convection and its parameterization'. Quart. J. Roy. Meteor. Soc., 100, 469-471.

Businger, J.A., J.C. Wyngaard, Y. Izumi, and E.F. Bradley, 1971: Flux-profile relationship in the atmospheric surface layer. J. Atmos. Sci., 28, 181-189.

Carl, M.D., T.C. Tarbell, and H.A. Panofsky, 1973: Profiles of wind and temperature from towers over homogeneous terrain. J. Atmos. Sci. 30, 788-794.

Caughey, S.J., and S.G. Palmer, 1979: Some aspects of turpulence structure through the depth of the convective boundary layer.

Deardorff, J.W., 1972: Numerical investigation of neutral and unstable planetary boundary layers. J. Atmos. Sci., 29, 91-115.

Deardorff, J.W., G.E. Willis, and B.H. Stockton, 1980: Laboratory studies of the entrainment zone of a convectively mixed layer. J. Fluid Mech., 100, 41-64.

Grant, A.L.M., 1986: Observations of boundary layer structure made during the 1981 KONTUR experiment. Quart. J. Roy. Meteor. Soc., 112, 825-841.

Kamada, R.F., 1988: A fractal interfacial entrainment model for dry convective boundary layers. part I: Model description. J. Atmos. Sci., 45, 17, 2365-2374.

\_\_\_\_\_, 1988: A fractal interfacial entrainment model for dry convective boundary layers. part II: Discussion of model behavior and comparison with other models. J. Atmos. Sci., 45, 17, 2375-2383.

Kato, H. and O.M. Phillips, 1969: On the penetration of a turbulent layer into stratified fluid. J. Fluid. Mech. 37, 643-655.

Mason, P.J. and D.J. Thompson, 1987: Large eddy simulations of the neutral-static-stability planetary boundary layer. Quart. J. Roy. Meteor. Soc., 113, 413-443.

Mahrt, L., and D.H. Lenschow, 1976: Penetrative convection at the top of a growing boundary layer. J. Atmos. Sci., 33,41-51.

Nelson, E., R. Stull, and E. Eloranta, 1989: A prognostic relationship for entrainment zone thickness, J. Appl. Meteorol., 28, 885-903.

Panofsky, H.A., and J.A. Dutton, 1984: Atmospheric Turbulence. Wiley and Sons, New York, p. 133.

Pollard, R.T., P.B. Rhines, and R.O.R.Y. Thompson, 1973: The deepening of the wind-mixed layer', Geophys. Fluid Dyn. 3, 381-404.

Sorbjan, Z., 1989: Structure of the Atmospheric Boundary Layer. Prentice-Hall, Englewood Cliffs, New Jersey, p. 74.

Tennekes, H., and A.G.M. Driedonks, 1981: Basic entrainment equations for the atmospheric boundary layer. Bound.-Layer Meteorol., 20, 515-531.

Turner, J.S., 1968: The influence of molecular diffusivity on turbulent entrainment across a density interface. J. Fluid Mech. 23, 639-656.

Wyngaard, J.C., 1985: Structure of the planetary boundary layer and implications for its modeling. J. Clim. Appl. Meteorol., 24, 1131-1142.

\_\_\_\_\_, 1988: Structure of the PBL. Lectures on Air Pollution Modeling, AMS, Boston, 1988, 25-29.

#### DISTRIBUTION LIST

		No.copies
1.	Defense Technical Information Center Cameron Station Alexandria, VA 22314	2
2.	Dudley Knox Library Naval Postgraduate School Monterey, CA 93943-5000	2
3.	Director of Research (08) Naval Postgraduate School Monterey, CA 93943-5000	1
4.	Dept. of Physics (PH) Naval Postgraduate School Monterey, CA 93943-5000	2
5.	Dr. Ray Kamada/061kd Naval Postgraduate School Monterey, CA 93943-5100	17
6.	Capt. David Struck (SSD/CLGR) Los Angeles AFB Los Angeles, CA 90009-2960	1
7.	Prof. Gordon Schacher Dean of Faculty and Graduate Studies Naval Postgraduate School Monterey, CA 93943-5100	1
8.	Capt. Mike Moss (AFESC/RDVS) Tyndall AFB, FL 32403-6001	1
9.	Lt. Col. Stephen Pryor (730 SPW) Vandenberg AFB, CA 93437-5000	1
10.	Mr. Steve Sambol (730 SPW/DOW) Vandenberg AFB, CA 93437-5000	1
11.	Mr. Randy Nyman ACTA Vandenberg AFB, CA 93437-5000	1
12.	Dr. Don Ermak Lawrence Livermore National Lab P.O. Box 808, L-262 Livermore, CA 94551	1
13.	Mr. Bruce Kunkel (PL/GPAA) Hanscom AFB, MA 01730-5000	1

14.	Mr. Bill Boyd (45 WS/WER) Patrick AFB, FL 32925-5000	1
15.	Mr. John Edwards SSD/DEV Los Angeles, AFB, CA 90009-2960	1
16.	Mr. Larry Mendenhall Geodynamics Corp. 21171 Western Ave Suite 100 Torrence, CA 90501	1
17.	Mr. Bart Lundblad (Aerospace/El Segundo) PO Box 92957 Los Angeles, CA 90009	1
18.	Mr. Jose Caraballo NASA Industrial Safety/RT-SOE KSC, Florida 39899	1
19.	Mr. Jan Zysko NASA PM-PCO-4 KSC, Florida 39899	1
20.	Dr. Tetsuji Yamada Yamada Science and Art 147 Monterey Bay Dr. S. Los Alamos, NM 87544	1
21.	Dr. D. Pepper 5301 N. Commerce #A Moorpark, CA 93021	1
22.	Dr. Roger Gibbs Naval Surface Warfare Center Dahlgren, Virginia 22448-5000	1
23.	Dr. Kenneth Moe USAF Space Division Box 92960 World Way Los Angeles, CA 90009-2960	1
24.	Dr. Torben Mikkelsen Meteorologie und Vind Energie Dept. RISO National Laboratory DK-4000 Roskilde, Denmark	1

25.	Dr. Neals Otto Jensen Meteorologie und Vind Energie Dept. RISO National Laboratory DK-4000 Roskilde, Denmark	1
26.	Dr. John C. Wyngaard Dept. of Meteorology Pennsylvania State University University Park, PA 16802	1
27.	Dr. Gary Geernert ONR, Office of the Chief of Naval Operations Arlington, VA 22217	1
28.	Dr. Ted Tsui Naval Research Laboratory Monterey, CA 93943-5006	1
29.	Dr. Steve Burke Naval Research Laboratory Monterey, CA 93943-5006	1
30.	Dr. Paul Gudiksen Lawrence Livermore National Lab P.O. Box 808, L-262 Livermore, CA 94551	1